



铝电解电容器

ALUMINUM ELECTROLYTIC CAPACITORS

产品一览表 / PRODUCT LIST

◆小型铝电解电容器 / MINIATURE ALUMINUM ELECTROLYTIC CAPACITORS

	系列名称 SERIES	特 长 FEATURES	通用 品 GENERAL PURPOS E	小型 化 品 MINIATU RIZE	薄型 化 品 LOW PROFI LE	低阻 抗 品 LOW IMPEDANC E	长 寿 命 品 LONG LIFE	RoHS COMPLIANCE	额定电压 RATED VOLTAGE (V.DC)	静 电 容 量 RATED CAPACITANCE (μF)	工作温度范围 CATEGORY TEMPERATURE RANGE (°C)
贴片品 V CHIP	NEW TKV	105°C 低ESR品 LOW ESR		●		●	●	●	6.3~35	100~1800	-55~+105
	TLV	105°C 低阻抗长寿命品 LOW IMPEDANCE, LONG LIFE		●		●	●	●	6.3~35	100~10000	-55~+105
	TZV	105°C 低阻抗品 LOW IMPEDANCE		●		●		●	6.3~50	4.7~1000	-55~+105
	JZV	105°C 低阻抗、高温回流焊对应品 LOW IMPEDANCE, HIGH TEMPERATURE REFLOW		●		●		●	6.3~35	4.7~1000	-55~+105
	SZV	※ 105°C 低阻抗品 LOW IMPEDANCE		●		●		●	6.3~35	1~100	-55~+105
	THV	125°C 低ESR、3000小时品 LOW ESR, 3000 HOURS		●		●	●	●	16~35	22~330	-40~+125
	TXV	125°C 低ESR品 LOW ESR		●		●	●	●	10~35	22~470	-40~+125
	SLV	105°C 5000小时品 5000 HOURS		●		●	●	●	6.3~50	0.1~100	-40~+105
	SJV	105°C 3000小时品 3000 HOURS		●		●	●	●	6.3~50	0.1~220	-40~+105
	SGV	105°C 2000小时品 2000 HOURS		●		●	●	●	6.3~50 63, 100	0.1~6800	-55~+105 -40~+105
JGV	105°C 2000小时、高温回流焊对应品 2000 HOURS, HIGH TEMPERATURE REFLOW		●		●	●	●	6.3~50	0.1~1000	-55~+105	
低阻抗品 LOW IMPEDANCE	UPGRADE ZLK	105°C 超高纹波电流、低阻抗品 ULTRA HIGH RIPPLE CURRENT, LOW IMPEDANCE		●		●	●	●	10~35	220~1800	-40~+105
	ZLJ	105°C 高纹波电流、长寿命品 HIGH RIPPLE CURRENT, LONG LIFE		●		●	●	●	6.3~100	8.2~8200	-40~+105
	ZLG	105°C 超低阻抗品 ULTRA LOW IMPEDANCE		●		●		●	6.3~35	4.7~3900	-40~+105
	ZLH	105°C 小型化、长寿命、低阻抗品 MINIATURIZED, LONG LIFE, LOW IMPEDANCE		●		●	●	●	6.3~100	8.2~8200	-40~+105
	ZL	105°C 高纹波电流、低阻抗品 HIGH RIPPLE CURRENT, LOW IMPEDANCE		●		●	●	●	6.3~100	5.6~6800	-40~+105
	ZT	125°C 1000~4000小时、低阻抗品 1000~4000 HOURS, LOW IMPEDANCE		●		●	●	●	10~35	22~2200	-40~+125
	NEW YXJ	105°C 小型化、长寿命、低阻抗品 MINIATURIZED, LONG LIFE, LOW IMPEDANCE		●	●	●	●	●	6.3~100	0.47~15000	-40~+105
	YXF	105°C 长寿命、低阻抗品 LONG LIFE, LOW IMPEDANCE		●	●	●	●	●	6.3~100	0.47~15000	-40~+105
YXG	105°C 高纹波电流、长寿命品 HIGH RIPPLE CURRENT, LONG LIFE		●	●	●	●	●	6.3~100	6.8~18000	-40~+105	
YXH	105°C 高纹波电流、长寿命品 HIGH RIPPLE CURRENT, LONG LIFE		●	●	●	●	●	6.3~100	6.8~18000	-40~+105	
长寿命品 LONG LIFE	BXF	105°C 高纹波电流、长寿命、高20mm以下品 HIGH RIPPLE CURRENT, LONG LIFE, 20mm Max		●	●		●	●	160~450	10~220	-25~+105
	BXC	105°C 高纹波电流、长寿命品 HIGH RIPPLE CURRENT, LONG LIFE		●			●	●	160~500	1~220	-25~+105
	BXA	105°C 长寿命品 LONG LIFE		●			●	●	160~450	6.8~220	-25~+105
	CFX	105°C 5000小时品 5000 HOURS		●			●	●	200~400	2.2~100	-25~+105
	RX50	150°C 1000小时品 1000 HOURS		●			●	●	10~63	47~1000	-40~+150
	RX30	130°C 1000~4000小时品 1000~4000 HOURS		●		●	●	●	10~100 200, 400	1~4700	-40~+130 -25~+130
	YXM	105°C 超小型化、10000小时品 ULTRA MINIATURIZED, 10000 HOURS		●	●		●	●	10~100	0.47~330	-25~+105
AC适配器用 For AC adapter	AX	105°C 超小型化品 ULTRA MINIATURIZED		●	●		●	●	400	4.7~15	-40~+105
薄型品 LOW PROFILE	ML	105°C 长寿命、薄型品 LONG LIFE, LOW PROFILE		●	●		●	●	6.3~50	1~1000	-40~+105
	WXA	105°C 高9mm~25mm品 9mm~25mm HEIGHT		●	●		●	●	6.3~50 160~250 350~450	1.5~10000	-55~+105 -40~+105 -25~+105
	WA	85°C 高9mm~25mm品 9mm~25mm HEIGHT		●	●		●	●	6.3~250 350~450	1.5~10000	-40~+85 -25~+85
	MH5	105°C 高5mm品 5mm HEIGHT		●	●		●	●	6.3~50	0.1~100	-40~+105
	MH7	105°C 高7mm品 7mm HEIGHT		●	●		●	●	6.3~50	0.1~100	-40~+105
	MS5	85°C 高5mm品 5mm HEIGHT		●	●		●	●	4~50	0.1~470	-40~+85
	MS7	85°C 高7mm品 7mm HEIGHT		●	●		●	●	4~63	0.1~470	-40~+85
标准品 GENERAL PURPOSE	PX	105°C 标准品 STANDARD		●	●		●	●	6.3~100 160~400 450	0.47~33000	-55~+105 -40~+105 -25~+105
	PK	85°C 标准品 STANDARD		●	●		●	●	6.3~400 450	0.47~33000	-40~+85 -25~+85
低漏电流品 LOW LEAKAGE CURRENT	TWL	85°C 低漏电流品 LOW LEAKAGE CURRENT		●			●	●	6.3~50	0.1~2200	-40~+85
双极性品 BI-POLAR	NXA	105°C 双极性标准品 STANDARD		●	●		●	●	6.3~50	0.47~1000	-55~+105
	NW5	85°C 双极性高5mm品 5mm HEIGHT		●	●		●	●	6.3~50	0.1~47	-40~+85
	NW7	85°C 双极性高7mm品 7mm HEIGHT		●	●		●	●	6.3~50	0.1~47	-40~+85
	NA	85°C 双极性标准品 STANDARD		●	●		●	●	6.3~100	0.47~1000	-40~+85
车载专用 FOR Automotive	HBX	※ 125°C 4000小时品、引线型 4000 HOURS, LEAD WIRE TYPE		●		●	●	●	25~250	18~5100	-40~+125
	HRX	※ 125°C 3000小时品、引线型 3000 HOURS, LEAD WIRE TYPE		●		●	●	●	25~50	470~5100	-55~+125
	HRV	※ 125°C 3000小时品、贴片型 3000 HOURS, SMD TYPE		●		●	●	●	25~50	470~5100	-55~+125

※了解更多详情，敬请咨询。Please contact our sales offices.



铝电解电容器

ALUMINUM ELECTROLYTIC CAPACITORS

产品一览表 / PRODUCT LIST

◆小型铝电解电容器 / MINIATURE ALUMINUM ELECTROLYTIC CAPACITORS

系列名称 SERIES	特长 FEATURES	通用型 GENERAL PURPOSE	小型薄型化品 MINIATURIZED	高纹波电流品 HIGH RIPPLE CURRENT	过电压对策规格设定品 FOR OVER VOLTAGE VENT TEST	长寿命品 LONG LIFE	对RoHS RoHS COMPLIANCE	额定电压 RATED VOLTAGE (V.DC)	静电容量 RATED CAPACITANCE (μF)	工作温度范围 CATEGORY TEMPERATURE RANGE (°C)
开关电源用 FOR SWITCHING POWER SUPPLY	TXW	105°C 10000小时、小型化品 10000 HOURS, MINIATURIZED	●			●	●	200~450	12~560	-25~+105
	CXW	105°C 5000小时、超小型化品 5000 HOURS, ULTRA MINIATURIZED	●			●	●	400~450	33~220	-25~+105
	QXW	105°C 超小型化品 ULTRA MINIATURIZED	●				●	400~450	27~220	-25~+105
	KXW	105°C 小型化品 MINIATURIZED		●				200~450	18~560	-25~+105
	SXW	过电压对策规格设定品 FOR OVER VOLTAGE VENT OPERATION TEST				●		200,400	4.7~330	-25~+105
	SAW	小型化过电压对策规格设定品 MINIATURIZED FOR OVER VOLTAGE VENT OPERATION TEST		●		●		400	18~120	-25~+105

◆大型铝电解电容器 / LARGE CAN TYPE ALUMINUM ELECTROLYTIC CAPACITORS

基板自立型 SNAP-IN TYPE	NEW VXS	105°C 5000小时 充电规格品 5000 HOURS, CHARGE-DISCHARGE SPECIFIED TYPE				●	●	315~450	82~1000	-25~+105
		MXH	105°C 超小型化品 ULTRA MINIATURIZED	●	●	●		400~450	100~820	-25~+105
	UPGRADE	MXG	105°C 小型化品 MINIATURIZED	●	●	●		50~100 160~500	680~15000 39~2700	-40~+105 -25~+105
		MXC	105°C 标准品 STANDARD	●				10~100 160~450	560~68000 47~2700	-40~+105 -25~+105
		HXC	105°C 高纹波电流品 HIGH RIPPLE CURRENT			●		200~450	68~2200	-25~+105
	UPGRADE	VXH	105°C 5000小时、小型化品 5000 HOURS, MINIATURIZED		●	●		200~450	100~2200	-25~+105
		VXG	105°C 5000小时品 5000 HOURS		●	●		10~100 200~450	560~56000 82~2200	-40~+105 -25~+105
		VXR	105°C 7000小时品 7000 HOURS			●		160~450	39~2200	-25~+105
	UPGRADE	KXF	105°C 高20mm小型化品 20mm HEIGHT, MINIATURIZED	●	●			10~100 160~450	330~10000 39~820	-40~+105 -25~+105
		SXG	过电压对策规格设定品 OVER-VOLTAGE VENTING SPECIFICATION			●		200, 400, 450	39~1200	-25~+105
		SXC	过电压对策规格设定品 OVER-VOLTAGE VENTING SPECIFICATION			●		200, 400	22~1500	-25~+105
		USH	85°C 超小型化品 ULTRA MINIATURIZED	●	●			400~450	120~1000	-25~+85
		USG	85°C 小型化品 MINIATURIZED	●	●	●		160~250 400~450	220~3300 68~820	-40~+85 -25~+85
		USC	85°C 标准品 STANDARD	●				10~250 315~450	180~82000 56~1000	-40~+85 -25~+85
	接头端子型 LUG TERMINAL TYPE	MXY	105°C 小型横置品 MINIATURIZED HORIZONTAL MOUNT		●			160~400	68~1500	-25~+105
螺栓端子型 SCREW TERMINAL TYPE	LSQ	85°C 螺栓端子标准品 STANDARD	●				10~100 160~450	2200~680000 270~33000	-40~+85 -25~+85	
	UPGRADE	LSU	85°C 螺栓端子小型化品 MINIATURIZED	●	●		350~500	1200~18000	-25~+85	
		LSW	105°C 螺栓端子标准品 STANDARD	●			10~100 160~400	2200~680000 220~22000	-40~+105 -25~+105	
		LSG	105°C 螺栓端子小型化品 MINIATURIZED	●	●		350~450	1000~18000	-25~+105	

◆闪光灯用铝电解电容器 / PHOTO FLASH ALUMINUM ELECTROLYTIC CAPACITORS

系列名称 SERIES	特长 FEATURES	对RoHS RoHS COMPLIANCE	额定电压 RATED VOLTAGE (V.DC)	静电容量 RATED CAPACITANCE (μF)	工作温度范围 CATEGORY TEMPERATURE RANGE (°C)
FK	接头端子标准品 STANDARD LUG TERMINAL	●	330 360	150~1500 150~1300	-20~+55
FKX	接头端子小型化品 MINIATURIZED LUG TERMINAL	●	330 360	150~1500	-20~+55
SF	接头端子高电压品 HIGH VOLTAGE LUG TERMINAL	●	450	150~1000	-20~+55
FW	引线端子 LEAD WIRE TERMINAL	●	330	10~300	-20~+60
CDF	接头端子闪光灯用 FOR FLASH LAMPS	●	360 450	60~400 40~300	-25~+70

◎注意 CAUTION

以上的闪光灯用铝电解电容器只用于照相摄影用闪光灯(电子闪光灯), 不能用作其它用途。

These Rubycon Photo Flash Capacitors are designed, manufactured and intended solely for use in photo flash and other photographic equipment. They are not intended for use in medical equipment.

Rubycon Corporation, Rubycon America, Inc., and Shin-Ei Capacitor Foil Company, Ltd. expressly disclaim any warranties or representations as to the suitability or fitness of these capacitors for use in medical equipment.